

ES36 - "Steam Master" Heavy Duty Commercial Steam Generator's Shop Drawing

Brand Name : Steam Master
Model : Executive Series – ES36
Dimensions : 29"L x 14"W x 24"H
Enclosure : Stainless Steel
Exclusive Features:
* A Self-Cleaning System
* Stand-By Binary System
* 2-in-1 Hands free system

Output : 36 KW
Electrical : 480V/600V;
Single or 3 Phase

24 Hour / 7 Day Digital Electronic
Timer or On/Off Switch

Automatic Power Clean Supply Line -
½" Copper pipe, a "Y" strainer, a
water pressure reducing valve (50PSI)
& a Shut Off Valve is required

Operational Water Supply Line: ¼" Copper tube. This line must
have a sediment filter and a Shut Off Valve

2 Steam-Out Pipes
1-1/4" Copper to each room

Power Junction box for
Power Supply Connection

LED Digital Thermostat and
Electronic Sensor

Motorized Gravity Drain Valve
1" Outlet Pipe



ES36 – “Steam Master” Heavy Duty Commercial Steam Generator’s Specifications

NAME	SPECIFICATIONS
Manufacturer	STEAM SAUNA INC.
Brand Name	Steam Master
Model	Executive Series – ES36
Output	36 KW
Room Size	Up to 2250 cubic feet
Electrical	480V/600V; Single Phase or 3 Phase
Operating Pressure	Atmospheric
24 Hour /7 Day Digital Timer	Factory Mounted, 20 programs setting for a day and a week
Thermostat	Electronic sensor wire connected with LED Digital Thermostat
Electronic Control Module	Contains a digital P.C. board that controls the multi-stage heating module, MIW water level sensing and self cleaning power flush system, programmed with an advanced technology digital microprocessor
Steam Control System	2-in-1 hands free system, standby binary system with 30-min E-touch Timer
Heating Elements	Low density industrial in-colony heating elements
Operational Water Feed	¼” inlet comes with compression connector for ¼” tube
Power Flush Valve	one - ½” inlet comes with compression connector for ½” Copper pipe.
Motorized Drain	Factory installed 1” motorized valve, connected on 1” stainless steel pipe comes with compression connector, run to the floor drain
Steam Outlets	2 outlets, comes with 1-¼” compression connector, branches for ¾” safety relief valve
Dimensions	29”L x 14”W x 24”H
Shipping/Operational Weight	Approximately 130 lbs / 150 lbs

ES42 - "Steam Master" Heavy Duty Commercial Steam Generator's Shop Drawing

Brand Name : Steam Master
Model : Executive Series – ES42
Dimensions : 29"L x 14"W x 24"H
Enclosure : Stainless Steel

Exclusive Features:

- * A Self-Cleaning System
- * Stand-By Binary System
- * 2-in-1 Hands free system

Output : 42 KW
Electrical : 480V/600V;
3 Phase

24 Hour / 7 Day Digital Electronic
Timer or On/Off Switch

Automatic Power Clean Supply Line -
½" Copper pipe, a "Y" strainer, a
water pressure reducing valve (50PSI)
& a Shut Off Valve is required

Operational Water Supply Line: ¼" Copper tube. This line must
have a sediment filter and a Shut Off Valve

2 Steam-Out Pipes
1-1/4" Copper to each room

Power Junction box for
Power Supply Connection

LED Digital Thermostat and
Electronic Sensor

Motorized Gravity Drain Valve
1" Outlet Pipe



ES42 – “Steam Master” Heavy Duty Commercial Steam Generator’s Specifications

NAME	SPECIFICATIONS
Manufacturer	STEAM SAUNA INC.
Brand Name	Steam Master
Model	Executive Series – ES42
Output	42 KW
Room Size	Up to 2400 cubic feet
Electrical	480V/600V; 3 Phase
Operating Pressure	Atmospheric
24 Hour /7 Day Digital Timer	Factory Mounted, 20 programs setting for a day and a week
Thermostat	Electronic sensor wire connected with LED Digital Thermostat
Electronic Control Module	Contains a digital P.C. board that controls the multi-stage heating module, MIW water level sensing and self cleaning power flush system, programmed with an advanced technology digital microprocessor
Steam Control System	2–in-1 hands free system, standby binary system with 30-min E-touch Timer
Heating Elements	Low density industrial in-colony heating elements
Operational Water Feed	¼” inlet comes with compression connector for ¼” tube
Power Flush Valve	one - ½” inlet comes with compression connector for ½” Copper pipe.
Motorized Drain	Factory installed 1” motorized valve, connected on 1” stainless steel pipe comes with compression connector, run to the floor drain
Steam Outlets	2 outlets, comes with 1-¼” compression connector, branches for ¾” safety relief valve
Dimensions	29”L x 14”W x 24”H
Shipping/Operational Weight	Approximately 130 lbs / 150 lbs

ES48 - "Steam Master" Heavy Duty Commercial Steam Generator's Shop Drawing

Brand Name : Steam Master
Model : Executive Series – ES48
Dimensions : 29"L x 14"W x 24"H
Enclosure : Stainless Steel
Exclusive Features:
* A Self-Cleaning System
* Stand-By Binary System
* 2-in-1 Hands free system

Output : 48 KW
Electrical : 480V/600V;
3 Phase

24 Hour / 7 Day Digital Electronic
Timer or On/Off Switch

Automatic Power Clean Supply Line -
½" Copper pipe, a "Y" strainer, a
water pressure reducing valve (50PSI)
& a Shut Off Valve is required

Operational Water Supply Line: ¼" Copper tube. This line must
have a sediment filter and a Shut Off Valve

2 Steam-Out Pipes
1-1/4" Copper to each room

Power Junction box for
Power Supply Connection

LED Digital Thermostat and
Electronic Sensor

Motorized Gravity Drain Valve
1" Outlet Pipe



ES48 – “Steam Master” Heavy Duty Commercial Steam Generator’s Specifications

NAME	SPECIFICATIONS
Manufacturer	STEAM SAUNA INC.
Brand Name	Steam Master
Model	Executive Series – ES48
Output	48 KW
Room Size	Up to 2685 cubic feet
Electrical	480V/600V; 3 Phase
Operating Pressure	Atmospheric
24 Hour /7 Day Digital Timer	Factory Mounted, 20 programs setting for a day and a week
Thermostat	Electronic sensor wire connected with LED Digital Thermostat
Electronic Control Module	Contains a digital P.C. board that controls the multi-stage heating module, MIW water level sensing and self cleaning power flush system, programmed with an advanced technology digital microprocessor
Steam Control System	2–in-1 hands free system, standby binary system with 30-min E-touch Timer
Heating Elements	Low density industrial in-colony heating elements
Operational Water Feed	¼” inlet comes with compression connector for ¼” tube
Power Flush Valve	one - ½” inlet comes with compression connector for ½” Copper pipe.
Motorized Drain	Factory installed 1” motorized valve, connected on 1” stainless steel pipe comes with compression connector, run to the floor drain
Steam Outlets	2 outlets, comes with 1-¼” compression connector, branches for ¾” safety relief valve
Dimensions	29”L x 14”W x 24”H
Shipping/Operational Weight	Approximately 130 lbs / 150 lbs

ES60 - "Steam Master" Heavy Duty Commercial Steam Generator's Shop Drawing

Brand Name : Steam Master
Model : Executive Series – ES60
Dimensions : 29"L x 14"W x 24"H
Enclosure : Stainless Steel
Exclusive Features:
* A Self-Cleaning System
* Stand-By Binary System
* 2-in-1 Hands free system

Output : 60 KW
Electrical : 480V/600V;
3 Phase

24 Hour / 7 Day Digital Electronic
Timer or On/Off Switch

Automatic Power Clean Supply Line -
½" Copper pipe, a "Y" strainer, a
water pressure reducing valve (50PSI)
& a Shut Off Valve is required

Operational Water Supply Line: ¼" Copper tube. This line must
have a sediment filter and a Shut Off Valve



2 Steam-Out Pipes
1-1/4" Copper to each room

Power Junction box for
Power Supply Connection

LED Digital Thermostat and
Electronic Sensor

Motorized Gravity Drain Valve
1" Outlet Pipe

ES60 – “Steam Master” Heavy Duty Commercial Steam Generator’s Specifications

NAME	SPECIFICATIONS
Manufacturer	STEAM SAUNA INC.
Brand Name	Steam Master
Model	Executive Series – ES60
Output	60 KW
Room Size	Up to 3285 cubic feet
Electrical	480V/600V; 3 Phase
Operating Pressure	Atmospheric
24 Hour /7 Day Digital Timer	Factory Mounted, 20 programs setting for a day and a week
Thermostat	Electronic sensor wire connected with LED Digital Thermostat
Electronic Control Module	Contains a digital P.C. board that controls the multi-stage heating module, MIW water level sensing and self cleaning power flush system, programmed with an advanced technology digital microprocessor
Steam Control System	2–in-1 hands free system, standby binary system with 30-min E-touch Timer
Heating Elements	Low density industrial in-colony heating elements
Operational Water Feed	¼” inlet comes with compression connector for ¼” tube
Power Flush Valve	one - ½” inlet comes with compression connector for ½” Copper pipe.
Motorized Drain	Factory installed 1” motorized valve, connected on 1” stainless steel pipe comes with compression connector, run to the floor drain
Steam Outlets	2 outlets, comes with 1-¼” compression connector, branches for ¾” safety relief valve
Dimensions	29”L x 14”W x 24”H
Shipping/Operational Weight	Approximately 130 lbs / 150 lbs